



THE INDUSTRY'S PREMIER LOW VOLTAGE LIGHTING TRANSFORMER

**100**<sup>WATT</sup>  
**MAGNETIC**



## FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS

## REQUIREMENTS

- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA AND CE REQUIREMENTS
- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411

## SPECIFICATIONS

PART NUMBER	PRIMARY VOLTAGE	OUTPUT VOLTAGE	BREAKERS	FREQUENCY	DIMENSIONS	WEIGHT
<b>CLASS 1</b>						
1022-12	120VAC-1A MAX	12VAC-8.33A MAX	1x10 A	60 Hz	6.75" x 5" x 4.75"	10 LBS.
1022-24	120VAC-1A MAX	24VAC-4.16A	1x5 A	60 Hz	6.75" x 5" x 4.75"	10 LBS.
<b>CLASS 2</b>						
1107	120VAC-1.3A MAX	12VAC-5A MAX	2x5 A	60 Hz	6.75" x 5" x 4.75"	10 LBS.
1111	120VAC-1A MAX	24VAC-4A MAX	1x4A	60 Hz	6.75" x 5" x 4.75"	10 LBS.