



THE INDUSTRY'S PREMIER LOW VOLTAGE LIGHTING TRANSFORMER

# DIRECT BURIAL



## FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS

## REQUIREMENTS

- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA AND CE REQUIREMENTS
- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411

## SPECIFICATIONS

100 WATT	CLASS 1	PRIMARY VOLTAGE	OUTPUT VOLTAGE	BREAKERS	FREQUENCY	DIMENSIONS
	1030	120VAC-1A MAX	12VAC-1x10A MAX	1x10 A	60 Hz	12" x 12" x 6"
	1030-277	277VAC-0.3A MAX	12VAC-1x10A MAX	1x10 A	60 Hz	12" x 12" x 6"
300 WATT	CLASS 1					
	1031	120VAC-2.7A MAX	12VAC-1x25A MAX	1x25 A	60 Hz	12" x 12" x 6"
	1031-277	277VAC-1.1A MAX	12VAC-1x25A MAX	1x25 A	60 Hz	12" x 12" x 6"
600 WATT	CLASS 1					
	1032	120VAC-5.5A MAX	12VAC-2x25A MAX	2x25 A	60 Hz	12" x 12" x 6"
	1032-277	277VAC-2.16A MAX	12VAC-2x25A MAX	2x25 A	60 Hz	12" x 12" x 6"