



THE INDUSTRY'S PREMIER LOW VOLTAGE LIGHTING TRANSFORMER



SLIM-TRAN

FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS

REQUIREMENTS

- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA AND CE REQUIREMENTS
- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411

SPECIFICATIONS

| 100 WATT | CLASS 1 | PRIMARY VOLTAGE | OUTPUT VOLTAGE | BREAKERS | FREQUENCY | DIMENSIONS |
|----------|------------|------------------|-----------------|----------|-----------|--------------------|
| | SL-100 | 120VAC-1A MAX | 12VAC-1x10A MAX | 1x10 A | 60 Hz | 8.75" x 6" x 3" |
| | SL-100-277 | 277VAC-0.3A MAX | 12VAC-1x10A MAX | 1x10 A | 60 Hz | 8.75" x 6" x 3" |
| 300 WATT | CLASS 1 | | | | | |
| | SL-300 | 120VAC-2.7A MAX | 12VAC-1x25A MAX | 1x25 A | 60 Hz | 8.75" x 6" x 3" |
| | SL-300-277 | 277VAC-1.1A MAX | 12VAC-1x25A MAX | 1x25 A | 60 Hz | 8.75" x 6" x 3" |
| 600 WATT | CLASS 1 | | | | | |
| | SL-600 | 120VAC-5.5A MAX | 12VAC-2x25A MAX | 2x25 A | 60 Hz | 8.75" x 6" x 3.75" |
| | SL-600-277 | 277VAC-2.16A MAX | 12VAC-2x25A MAX | 2x25 A | 60 Hz | 8.75" x 6" x 3.75" |